PILATO






The rounded front, beautifully sloping angles and stainless steel finish of Pilato make a striking visual statement. Available in 30" or 36" widths, Pilato features include a powerful 600 CFM blower, 2 LED lights , dishwasher safe stainless steel microhole filters and multi-function electronic controls with LCD display that deliver convenience and safety.

Designed for standard ducted installation, Pilato can also be installed as a recirculating system using the Recirculating Kit, available as an accessory.





	EPL630S2	EPL636S2	
A	30" (76.2 cm)	36" (91.2cm)	
В	21 ½" (54.7 cm)		
C*	Min: 28 7/8 (73.3cm) Max: 42 1/16(106.9cm)		
D**	Min: 28 ³ /⁄ (72 cm) Max: 38" (96.6 cm)		
Е	6" (15.9 cm)		
F	10" (25.4cm)		
G	24 1/8 (61cm)		
Н	1½" (4cm)		
I	7 ½" (18.4cm)		
J	8 ½ (20.7cm)		

^{*} Ductless (Recirculating) version

^{**} Ducted version

PILATO









SPECIFICATIONS

Width:	30" UNIT	36" UNIT		
Model:	EPL630S2	EPL636\$2		
Dimensions:	30" W x 21 1/2" D x min 28 3/8" max 42 1/16"H	36" W x 21 1/2" D x min 28 3/8" max 42 1/16"H		
Blower Type(internal):**	600 CFM (3-sp	600 CFM (3-speed + boost)		
Noise (sones):**	6.8 sones			
Finish:	Stainless Steel			
Controls:	Multi-function electronic with LCD display			
Illumination:	2 LED, 6.5 W, 3000 K			
Grease Filter:	Dishwasher-safe Stainless Steel Microhole Filter (2 w/30" & 3 w/36")			
Duct Transition:	Round 6" Top Discharge			
Installation Type:	Ducted or Recirculating (Kit sold separately)			
Telescopic Chimney:		of min 7'5", max 9'2" (ducted out) & ax 9'5" (recirculating).		
Electrical:	120V-60 Hz, 450 W			
KITS:	KIT02766 (Contains 6"			
Recirculating Kit	Deflector and 2 Round Carbon Filters)			
Long Chimney Extension:	KIT02762 (Can reach 8'5" - 11'3'	(Can reach 8'5" - 11'3" (ducted), 8'7" - 11'7" (recirculating)		
WARRANTY:*** Two (2) Years Parts & In-Home Labor. Earn an add of Parts & In-Home Labor by registering of				

PLUS FEATURES



CFM REDUCTION - CFM Reduction System (CRS), is an exclusive feature to Elica hoods, which enables the user to reduce the maximum blower CFM, to meet local code requirements.



LED LIGHT - LED lighting is undoubtedly the smartest solution in terms of energy saving. Expected life is over 20,000 hours, and should last the full life of the hood.



HUSH SYSTEM - An exclusive sound deadening technology that effectively reduces sound levels up to 35%, compared to typical range



CLEAN FILTER ALARM - When activated, your hood will emit a "beep" signal to let you know when is time to clean your filters. For some models, an intermittent light remain active until cleaning filter action is completed. See instrucions manual to activate feature.



TOP PERFORMANCE - Excellent performance for models equipped with this plus. High fume capturing capacity with an average aspiration range of 600 CFM's. with low noise levels, 1.2 - 1.7 sones at working speed.



REPLACE FILTER ALARM - When activated, your hood will emit a "beep" signal to let you know when is time to replace carbon filters. See instrcutions manual to activate feature.

HVI Certified Ratings	High Speed	Working Speed	Duct Size
CFM	450	150	6" (Vertical)
Sones	12	2	6" (Vertical)

^{*} The product images shown are for illustration purposes only and may not be an exact representation of the product.

^{**} Blower performance indicates the performance of the blower by itself. Performance claims are not HVI certified but were established in accordance with HVI Standardized test procedure. For Certified Ratings, please refer to HVI Certified Product Directory. Electric Ratings are declared according to UL.

^{***} For valid warranty extension, register within 3 months from purchase. For USA & Canada Users Only.