



Ref. Certif. No.

DK-146085-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Range Hood
Name and address of the applicant	Elica SPA Via Ermanno Casoli 2 Fabriano, AN, 60044 Italy
Name and address of the manufacturer	Elica SPA Via Ermanno Casoli 2 Fabriano, AN, 60044 Italy
Name and address of the factory	Elica SPA Localita Montirone Mergo, AN, 60030 Italy <input checked="" type="checkbox"/> Additional Information on page 2
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	220-240 or 230 V 50-60 Hz, 220-240 or 230V 50 Hz, 220-230 or 230 V 50-60 Hz, 220 V 60 Hz and 110-127 V or 120 V 60 Hz. <input checked="" type="checkbox"/> Additional Information on page 2-4
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	CTF Stage 3
Model / Type Ref.	E015A II, E015C II <input checked="" type="checkbox"/> Additional Information on page 2-4
Additional information (if necessary may also be reported on page 2)	National Differences: EU Group Differences, AU, DK, FI, NZ, NO, SE, GB <input checked="" type="checkbox"/> Additional Information on page 4
A sample of the product was tested and found to be in conformity with	IEC 60335-2-31:2012, IEC 60335-2-31:2012/AMD1:2016, IEC 60335-2-31:2012/AMD2:2018, IEC 60335-1:2010, IEC 60335-1:2010/AMD1:2013, IEC 60335-1:2010/AMD2:2016
As shown in the Test Report Ref. No. which forms part of this Certificate	23-4790731357.17.1 issued on 2023-10-09

This CB Test Certificate is issued by the National Certification Body




- UL Solutions (US), 333 Pflugsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/nbcnames

Date: 2023-10-13

Signature:


Thomas Wilson



Ref. Certif. No.

DK-146085-UL

Factory(ies):

ELICA GROUP POLSKA SP Z O O
Ul Inzynierska 3 Jelcz Laskowice, 55-221
Poland

Additional Model and Ratings Detail(s):

ADDITIONAL INFORMATION							
Type/Code identification							
This Test Report covers the following types and associated codes identifying the Electrical Configuration Type: E015A II or E015C II + Code , (i.e. E015A II 1S25AG 2B S B))							
No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric hob/Gas hob (cm)	Distance from Electric hob/Gas hob (cm) (AUS/NZL)
1	E015A II	1K20 2B S B	106	220-240 or 230	50-60	50/65	60/65
2	E015A II	1K28A 1B P B	118	220-240 or 230	50-60	50/65	60/65
3	E015A II	1K28A 1B S B	118	220-240 or 230	50-60	50/65	60/65
4	E015A II	1K28A 2B P B	121	220-240 or 230	50-60	50/65	60/65
5	E015A II	1K28A 2B S B	121	220-240 or 230	50-60	50/65	60/65
6	E015A II	1K37A 1B P B	118	220-240 or 230 220	50 60	50/65	60/65 -
7	E015A II	1K37A 1B S B	118	220-240 or 230 220	50 60	50/65	60/65 -
8	E015A II	1K37A 2B P B	121	220-240 or 230 220	50 60	50/65	60/65 -
9	E015A II	1K37A 2B S B	121	220-240 or 230 220	50 60	50/65	60/65 -
10	E015A II	1S25 1B P B	163	220-240 or 230	50-60	50/65	60/65
11	E015A II	1S25 1B S B	163	220-240 or 230	50-60	50/65	60/65
12	E015A II	1S25 2B P B	166	220-240 or 230	50-60	50/65	60/65
13	E015A II	1S25 2B S B	166	220-240 or 230	50-60	50/65	60/65

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-10-13

Signature:

Thomas Wilson



Ref. Certif. No.

DK-146085-UL

Additional Model and Ratings Detail(s) (CONT'D):

ADDITIONAL INFORMATION							
No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric hob/Gas hob (cm)	Distance from Electric hob/Gas hob (cm) (AUS/NZL)
14	E015A II	1S25AG 1B P B	143	220-240 or 230	50-60	50/65	60/65
15	E015A II	1S25AG 1B S B	143	220-240 or 230	50-60	50/65	60/65
16	E015A II	1S25AG 2B P B	146	220-240 or 230	50-60	50/65	60/65
17	E015A II	1S25AG 2B S B	146	220-240 or 230	50-60	50/65	60/65
18	E015A II	1S25 2E P B	165	220-240 or 230	50-60	50/65	60/65
19	E015A II	1S25 2E S B	165	220-240 or 230	50-60	50/65	60/65
20	E015A II	1S25AG 2E P B	145	220-240 or 230	50-60	50/65	60/65
21	E015A II	1S25AG 2E S B	145	220-240 or 230	50-60	50/65	60/65
22	E015C II	1K20 1B P B	103	220-230 or 230	50-60	50/65	60/65
23	E015C II	1K20 1B S B	103	220-240 or 230	50-60	50/65	60/65
24	E015C II	1K20 2B P B	106	220-230 or 230	50-60	50/65	60/65
25	E015C II	1K20 2B S B	106	220-230 or 230	50-60	50/65	60/65
26	E015C II	1K28 1B P B	98	220-240 or 230	50-60	50/65	60/65
27	E015C II	1K28 1B S B	98	220-240 or 230	50-60	50/65	60/65
28	E015C II	1K28 2B P B	101	220-240 or 230	50-60	50/65	60/65
29	E015C II	1K28 2B S B	101	220-240 or 230	50-60	50/65	60/65
30	E015C II	1K28 1B P E	123	110-127 or 120	60	50/65	-
31	E015C II	1K28 1B S E	123	110-127 or 120	60	50/65	-
32	E015C II	1K28 2B P E	126	110-127 or 120	60	50/65	-
33	E015C II	1K28 2B S E	126	110-127 or 120	60	50/65	-

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-10-13

Signature:

Thomas Wilson



Ref. Certif. No.

DK-146085-UL

Additional Model and Ratings Detail(s) (CONT'D):

ADDITIONAL INFORMATION	
Explanation of type/electrical configuration:	
E015A, E015C	= Type of construction
II	= Insulation Class
xKy or xSy	= Number of Motors and Type of Motor
xE or xB	= Number and kind of lamps ("E" Led Spot Lamp 2,5 W or "B" Bulb Led Lamp 3 W)
P or S	= Kind of Controls ("P" Push button or "S" Slider switch)
B or E	= "B": tested for/at 240V) or "E": tested for/at 110-127 or 120 V
Remark: x is a number (one or more digit(s)), y is a sequence of alphanumeric characters of any length.	

Additionally evaluated to:

EN 60335-1:2012, EN 60335-1:2012/A11:2014, EN 60335-1:2012/A13:2017, EN 60335-1:2012/A1:2019, EN 60335-1:2012/A14:2019, EN 60335-1:2012/A2:2019, EN 60335-1:2012/A15:2021, EN 60335-2-31:2014, EN 62233:2008

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-10-13

Signature:

Thomas Wilson