




Ref. Certif. No.

**DK-158972-UL**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

**CB TEST CERTIFICATE**

Product	Range Hood
Name and address of the applicant	Elica SPA Via Ermanno Casoli 2 Fabriano, AN, 60044 Italy
Name and address of the manufacturer	Elica SPA Via Ermanno Casoli 2 Fabriano, AN, 60044 Italy
Name and address of the factory	Elica SPA Localita Montirone Mergo, AN, 60030 Italy
Note: When more than one factory, please report on page 2	<input checked="" type="checkbox"/> <a href="#">Additional Information on page 2</a>
Ratings and principal characteristics	220-240 or 230 V 50-60 Hz, 220-240 or 230 V 50 Hz, 220 V 60 Hz, 110-127 V 60 Hz, 127 V 60 Hz, 110 V 60 Hz, Max 460 W (see CB Test Report for details)
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	CTF Stage 2
Model / Type Ref.	E100D I, E100E I <input checked="" type="checkbox"/> <a href="#">Additional Information on page 2 to 9</a>
Additional information (if necessary may also be reported on page 2)	National Differences: EU Group Differences, AU, DK, FI, NZ, NO, SE, GB <input checked="" type="checkbox"/> <a href="#">Additional Information on page 9</a>
A sample of the product was tested and found to be in conformity with	IEC 60335-2-31:2012, IEC 60335-2-31:2012/AMD1:2016, IEC 60335-2-31:2012/AMD2:2018, IEC 60335-1:2010, IEC 60335-1:2010/AMD1:2013, IEC 60335-1:2010/AMD2:2016
As shown in the Test Report Ref. No. which forms part of this Certificate	24-4791266968.14.1 issued on 2024-10-14

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:  
Thomas Wilson



Ref. Certif. No.

DK-158972-UL

Factory(ies):

ELICA GROUP POLSKA SP Z O O
Ul Inzynierska 3 Jelcz Laskowice 55-221
Poland

Additional Model and Ratings Detail(s):

Table with 8 columns: No., Type, Code (Electrical Configuration), Rated Input (W), Rated Voltage (V), Frequency (Hz), Distance from Electric Hob/Gas Hob (cm), Distance from Electric Hob/Gas Hob (cm) AUS/NZL. Rows 1-22 list various model configurations and their specifications.

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-10-29

Signature:

Handwritten signature of Thomas Wilson

Thomas Wilson



Ref. Certif. No.

**DK-158972-UL**

**Additional Model and Ratings Detail(s):**

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
23	E100E I	1S40AF 4E CT B	270	220-240 or 230	50-60	50/65	60/65
24	E100E I	1S40AF 4E T B	270	220-240 or 230	50-60	50/65	60/65
25	E100D I	1S40AC 2H TE E	340 **	110-127	60	60/65	-
26	E100D I	1S50AC 2H T C	460	110	60	65/65	-
27	E100D I	1S40BD 2E R B	255	220-240 or 230 220	50 60	50/65	60/65 -
28	E100D I	1S40BD 2E T B	255	220-240 or 230 220	50 60	50/65	60/65 -
29	E100D I	1S40BD 2E CT B	255	220-240 or 230 220	50 60	50/65	60/65 -
30	E100D I	1S40BD 3E T B	268	220-240 or 230 220	50 60	50/65	60/65 -
31	E100D I	1S40BD 4E CT B	260	220-240 or 230 220	50 60	50/65	60/65 -
32	E100D I	1S40BF 2E R B	265	220-240 or 230 220	50 60	50/65	60/65 -
33	E100D I	1S40BF 2E T B	265	220-240 or 230 220	50 60	50/65	60/65 -
34	E100D I	1S40BF 2E CT B	265	220-240 or 230 220	50 60	50/65	60/65 -
35	E100D I	1S40BF 3E CT B	278	220-240 or 230 220	50 60	50/65	60/65 -
36	E100D I	1S40BF 4E CT B	270	220-240 or 230 220	50 60	50/65	60/65 -
37	E100D I	1S48BD 2E R B	225	220-240 or 230	50	50/65	60/65
38	E100D I	1S48BD 2E T B	225	220-240 or 230	50	50/65	60/65
39	E100D I	1S48BD 2E CT B	225	220-240 or 230	50	50/65	60/65
40	E100D I	1S48BD 3E T B	228	220-240 or 230	50	50/65	60/65
41	E100D I	1S48BD 4E CT B	230	220-240 or 230	50	50/65	60/65

**Additional information (if necessary)**



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson



Ref. Certif. No.

**DK-158972-UL**

**Additional Model and Ratings Detail(s):**

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
42	E100D I	1SI45BG 2E R B	265	220-240 or 230	50	50/65	60/65
43	E100D I	1SI45BG 2E T B	265	220-240 or 230	50	50/65	60/65
44	E100D I	1SI45BG 2E CT B	265	220-240 or 230	50	50/65	60/65
45	E100D I	1SI45BG 3E T B	268	220-240 or 230	50	50/65	60/65
46	E100D I	1SI50BB 2E R B	305	220-240 or 230	50	50/65	60/65
47	E100D I	1SI50BB 2E T B	305	220-240 or 230	50	50/65	60/65
48	E100D I	1SI50BB 2E CT B	305	220-240 or 230	50	50/65	60/65
49	E100D I	1SI50BB 3E T B	308	220-240 or 230	50	50/65	60/65
50	E100E I	1S40BD 4E T B	260	220-240 or 230 220	50 60	50/65	60/65 -
51	E100E I	1S40BD 4E TE B	260	220-240 or 230 220	50 60	50/65	60/65 -
52	E100E I	1S40BD 4E CT B	260	220-240 or 230 220	50 60	50/65	60/65 -
53	E100E I	1S40BF 4E T B	270	220-240 or 230 220	50 60	50/65	60/65 -
54	E100E I	1S40BF 4E TE B	270	220-240 or 230 220	50 60	50/65	60/65 -
55	E100E I	1S40BF 4E CT B	270	220-240 or 230 220	50 60	50/65	60/65 -
56	E100E I	1S48BD 4E T B	230	220-240 or 230	50	50/65	60/65
57	E100E I	1S48BD 4E TE B	230	220-240 or 230	50	50/65	60/65
58	E100E I	1S48BD 4E CT B	230	220-240 or 230	50	50/65	60/65
59	E100E I	1SI45BG 4E T B	270	220-240 or 230	50	50/65	60/65
60	E100E I	1SI45BG 4E TE B	270	220-240 or 230	50	50/65	60/65
61	E100E I	1SI45BG 4E CT B	270	220-240 or 230	50	50/65	60/65
62	E100E I	1SI50BB 4E T B	310	220-240 or 230	50	50/65	60/65
63	E100E I	1SI50BB 4E TE B	310	220-240 or 230	50	50/65	60/65
64	E100E I	1SI50BB 4E CT B	310	220-240 or 230	50	50/65	60/65
65	E100E I	1S40BD 2E TE B	255	220-240 or 230 220	50 60	50/65	60/65
66	E100E I	1S40BF 2E TE B	265	220-240 or 230 220	50 60	50/65	60/65

**Additional information (if necessary)**



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson



Ref. Certif. No.

DK-158972-UL

Additional Model and Ratings Detail(s):

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
67	E100E I	1S48BD 2E TE B	225	220-240 or 230	50	50/65	60/65
68	E100D I	1S40BB 2E R D	255	220	60	50/65	-
69	E100D I	1S40BB 2E T D	255	220	60	50/65	-
70	E100D I	1S40BB 2E CT D	255	220	60	50/65	-
71	E100D I	1S40BB 3E T D	258	220	60	50/65	-
72	E100D I	1S40BB 4E CT D	260	220	60	50/65	-
73	E100E I	1S40BB 2E TE D	255	220	60	50/65	-
74	E100E I	1S40BB 4E CT D	260	220	60	50/65	-
75	E100E I	1S40BB 4E T D	260	220	60	50/65	-
76	E100E I	1S40BB 4E TE D	260	220	60	50/65	-
77	E100D I	1S40BB 2E ASC D	255	220	60	50/65	-
78	E100D I	1SI45AC 2E T B	265	220-240 or 230	50	50/65	60/65
79	E100E I	1SI45AC 2E T B	265	220-240 or 230	50	50/65	60/65
80	E100E I	1SI45AC 4E T B	270	220-240 or 230	50	50/65	60/65
81	E100D I	1S35CB 2E T B	180	220-240 or 230	50-60	50/65	60/65
82	E100D I	1S35CB 2E TE B	180	220-240 or 230	50-60	50/65	60/65
83	E100D I	1S40CB 2E T B	255	220-240 or 230 220	50 60	50/65	60/65 -
84	E100D I	1S40CB 2E T1 B	255	220-240 or 230 220	50 60	50/65	60/65 -
85	E100D I	1S40CG 2E T B	255	220-240 or 230 220	50 60	50/65	60/65 -
86	E100D I	1S48CD 2E T B	205	220-240 or 230	50-60	50/65	60/65
87	E100D I	1S48CD 2E TH B	205	220-240 or 230	50-60	50/65	60/65
88	E100D I	1SI40CC 2E T B	315	220-240 or 230	50	50/65	60/65
89	E100D I	1SI40CC 2E T1 B	315	220-240 or 230	50	50/65	60/65
90	E100D I	1SI45CG 2E T B	265	220-240 or 230	50	50/65	60/65
91	E100D I	1S40BF 2E IT B	265	220-240 or 230 220	50 60	50/65	60/65 -
92	E100D I	1S40BF 3E T B	268	220-240 or 230 220	50 60	50/65	60/65 -
93	E100E I	1S40CB 2E TE B	255	220-240 or 230 220	50 60	50/65	60/65 -

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson



Ref. Certif. No.

**DK-158972-UL**

**Additional Model and Ratings Detail(s):**

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
94	E100E I	1S40CB 4E CT B	260	220-240 or 230 220	50 60	50/65	60/65 -
95	E100E I	1S40CB 4E T B	260	220-240 or 230 220	50 60	50/65	60/65 -
96	E100E I	1S40CB 4E TE B	260	220-240 or 230 220	50 60	50/65	60/65 -
97	E100E I	1S40CB 4E T1 B	260	220-240 or 230 220	50 60	50/65	60/65 -
98	E100E I	1S40CF 4E T B	270	220-240 or 230	50-60	50/65	60/65
99	E100E I	1S40CG 4E T B	260	220-240 or 230 220	50 60	50/65	60/65 -
100	E100E I	1S48CD 4E CT B	210	220-240 or 230	50-60	50/65	60/65
101	E100E I	1S48CD 4E T B	210	220-240 or 230	50-60	50/65	60/65
102	E100E I	1S48CD 4E TE B	210	220-240 or 230	50-60	50/65	60/65
103	E100E I	1S48CD 4E TH B	210	220-240 or 230	50-60	50/65	60/65
104	E100E I	1SI40CC 4E T1 B	320	220-240 or 230	50	50/65	60/65
105	E100E I	1SI45CG 4E CT B	270	220-240 or 230	50	50/65	60/65
106	E100E I	1SI45CG 4E T B	270	220-240 or 230	50	50/65	60/65
107	E100E I	1S40BF 2E IT B	265	220-240 or 230 220	50 60	50/65	60/65 -
108	E100E I	1SI50BB 4E R B	310	220-240 or 230	50	50/65	60/65
109	E100D I	1S40BD 2E TH B	255	220-240 or 230 220	50 60	50/65	60/65 -
110	E100E I	1S40BD 4E TH B	260	220-240 or 230 220	50 60	50/65	60/65 -
111	E100E I	1S40AC 2E T B	255	220-240 or 230	50-60	50/65	60/65
112	E100D I	1S40CB 2E CT1 B	255	220-240 or 230 220	50 60	50/65	60/65 -
113	E100D I	1SI40CC 2E CT1 B	315	220-240 or 230	50	50/65	60/65
114	E100D I	1S40CB 2E CT B	255	220-240 or 230 220	50 60	50/65	60/65 -

**Additional information (if necessary)**



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson



Ref. Certif. No.

**DK-158972-UL**

**Additional Model and Ratings Detail(s):**

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
115	E100D I	1S40BL 2E T E	265	127	60	50/65	-
116	E100D I	1S40BL 2E CT E	265	127	60	50/65	-
117	E100E I	1S40BL 2E T E	265	127	60	50/65	-
118	E100E I	1S40BB 2E T D	255	220	60	50/65	-
119	E100E I	1S40BF 2E T B	265	220-240 or 230 220	50 60	50/65	60/65 -
120	E100E I	1S40BL 4E CT E	270	127	60	50/65	-
121	E100D I	1S35AC 2E TE B	180	220-240 or 230	50-60	50/65	60/65
122	E100D I	1S40BD 2E TE B	255	220-240 or 230 220	50 60	50/65	60/65 -
123	E100D I	1SI40CC 2E BCT B	315	220-240 or 230	50	50/65	60/65
124	E100E I	1SI40CC 4E BCT B	320	220-240 or 230	50	50/65	60/65
125	E100E I	1S40CB 2E T B	255	220-240 or 230 220	50 60	50/65	60/65 -
126	E100E I	1S48CD 2E T B	205	220-240 or 230	50-60	50/65	60/65
127	E100D I	1S40AC 2E T E	235 **	110-127	60	60/65	-
128	E100D I	1S40AC 3E T E	237,5 **	110-127	60	60/65	-
129	E100E I	1S40AC 4E T E	240 **	110-127	60	60/65	-
130	E100D I	1S40AC 2E CT B	255	220-240 or 230	50	50/65	60/65
131	E100D I	1S48CB 2E CT B	275	220-240 or 230 220	50 60	50/65	60/65 -
132	E100D I	1S40CB 2E R B	255	220-240 or 230 220	50 60	50/65	60/65 -
133	E100E I	1S48CB 4E CT B	280	220-240 or 230 220	50 60	50/65	60/65 -
134	E100E I	1S40CB 4E R B	260	220-240 or 230 220	50 60	50/65	60/65 -
135	E100D I	1S48CD 2E R B	205	220-240 or 230	50-60	50/65	60/65
136	E100E I	1S40CB 2E T1 B	255	220-240 or 230 220	50 60	50/65	60/65 -

**Additional information (if necessary)**



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson



Ref. Certif. No.

**DK-158972-UL**

**Additional Model and Ratings Detail(s):**

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
137	E100D I	1S48CB 1SE CT B	277	220-240 or 230 220	50 60	50/65	60/65 -
138	E100E I	1S48CB 2SE CT B	277	220-240 or 230 220	50 60	50/65	60/65 -
139	E100E I	1S40BF 4EP CT B	265	220-240 or 230 220	50 60	50/65	60/65 -
140	E100E I	1S40BF 4EP T B	265	220-240 or 230 220	50 60	50/65	60/65 -
141	E100E I	1S40BF 4EP TE B	265	220-240 or 230 220	50 60	50/65	60/65 -
142	E100E I	1S40CB 4EP CT B	255	220-240 or 230 220	50 60	50/65	60/65 -
143	E100E I	1S40CB 4EP T B	255	220-240 or 230 220	50 60	50/65	60/65 -
144	E100E I	1S40CB 4EP TE B	255	220-240 or 230 220	50 60	50/65	60/65 -
145	E100E I	1S48CD 4EP CT B	205	220-240 or 230	50-60	50/65	60/65
146	E100E I	1S48CD 4EP T B	205	220-240 or 230	50-60	50/65	60/65
147	E100E I	1S48CD 4EP TE B	205	220-240 or 230	50-60	50/65	60/65
148	E100E I	1S48CB 4EP CT B	275	220-240 or 230 220	50 60	50/65	60/65 -
149	E100E I	1S48CB 4EP T B	275	220-240 or 230 220	50 60	50/65	60/65 -
150	E100D I	1S48CB 2E CT1 B	275	220-240 or 230 220	50 60	50/65	60/65 -
151	E100D I	1S48CD 1SE CT B	207	220-240 or 230	50-60	50/65	60/65
152	E100D I	1S48CB 1SE ASC1 B	277	220-240 or 230 220	50 60	50/65	60/65 -

**Additional information (if necessary)**



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson





Ref. Certif. No.

**DK-158972-UL**

**Additional Model and Ratings Detail(s):**

No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric Hob/Gas Hob (cm)	Distance from Electric Hob/Gas Hob (cm) AUS/NZL
153	E100D I	1S48CB 2E BCT B	275	220-240 or 230 220	50 60	50/65	60/65 -
154	E100E I	1S48CB 4EP R B	275	220-240 or 230 220	50 60	50/65	60/65 -
155	E100D I	1S48CB 1SE BWCT B	277	220-240 or 230 220	50 60	50/65	60/65 -
156	E100E I	1S48CB 2SE BWCT B	277	220-240 or 230 220	50 60	50/65	60/65 -

Remark: \*\* Rated Input referring to all the voltages of rated voltage range 110-127 V. See CB Test Report Table 10.1 for acceptable deviation.

**Explanation of type/electrical configuration:**

E100D or E100E	= Type of construction
I	= Insulation Class
xSy	= Number of Motors and Type of Motor ("K" Shaded pole or "S" Capacitor Motor)
xH, xE, xSE or xEP	= Number and kind of lamps ("H" low voltage halogen lamps 20 W, "E" LED spot Lamp 2,5 W, "SE" Strip LED 7 W or "EP" LED spot lamps connected in parallel in pairs max power input of each pair: 2,5 W).
CT, TE, T, ASC, R, T1, TH, IT, CT1, BCT, ASC1 or BWCT	= Kind of Control ("CT" Capacitive Touch control, "TE" Electro-mechanic Touch Control, "T" Touch Control, "ASC" Air Sensor Capacitive Touch control, "R" Rotating Touch Control), "T1" Touch Control with soft first speed, "TH" Touch Control H2H, "IT" Infrared Touch Control, "CT1" Capacitive Touch control with soft first speed, "BCT" Bluetooth Capacitive Touch Control, "ASC1" Air Sensor Capacitive Touch control with soft first speed or "BWCTB"
B, C, D or E	= For UK (tested for/at 240V, "B") or Voltage Ratings 110 V ("C"), 220 V ("D"), 110-127 V or 127 V ("E").

Remark: x is a number (one or more digit), y is a sequence of alphanumerical characters of any length.

**Additionally evaluated to:**

EN 60335-1:2012, EN 60335-1:2012/A11:2014, EN 60335-1:2012/A13:2017, EN 60335-1:2012/A1:2019, EN 60335-1:2012/A14:2019, EN 60335-1:2012/A2:2019, EN 60335-1:2012/A15:2021, EN 60335-1:2012/A16:2023, EN 60335-2-31:2014, EN 60335-2-31:2014/A1:2023, EN 60335-2-31:2014/A2:2023, EN 60335-2-31:2014/A11:2023, EN 62233:2008

**Additional information (if necessary)**



- UL Solutions (US), 333 Pflingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-10-29

Signature:

Thomas Wilson