

	Ref. Certif. No.
	DK-72890-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	Range Hood
Name and address of the applicant	Elica SPA VIA ERMANNO CASOLI 2 FABRIANO, 60044 AN Italy
Name and address of the manufacturer	Elica SPA VIA ERMANNO CASOLI 2 FABRIANO, 60044 AN Italy
Name and address of the factory	ELICA GROUP POLSKA SP Z O O UL INZYNIERSKA 3 JELCZ LASKOWICE, 55-221 Poland
	<input checked="" type="checkbox"/> Additional Information on page 3
Ratings and principal characteristics	220-240 or 230V 50/60Hz, 110V 60Hz, 220-240 or 230V 50Hz, 220V 60Hz, max 331 W See page 2
Trademark (if any)	Elica
Type of Customer's Testing Facility (CTF) Stage used	CTF Stage 3
Model / Type Ref.	E124 I See Page 2
Additional information (if necessary may also be reported on page 2)	<input checked="" type="checkbox"/> Additional Information on page 3
A sample of the product was tested and found to be in conformity with	IEC 60335-1(ed.5), IEC 60335-2-31(ed.5)
As shown in the Test Report Ref. No. which forms part of this Certificate	4788430047.3.1 issued on 2018-05-04

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

Date: 2018-05-08

Signature:

For full legal entity names see www.ul.com/ncbnames

Jan-Erik Storgaard

		Ref. Certif. No.
		DK-72890-UL

Model details:

Type/Code identification						
This Test Report covers the following type and associated code identifying the Electrical configuration: Type: E124 I + Code , (i.e. E124 I 1S35AC 2A P B)						
No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric/gas Hob (cm)
1	E124 I	1S35AC 2A P B	231	220-240 or 230	50/60	50/65
2	E124 I	1S35AC 2A T B	231	220-240 or 230	50/60	50/65
3	E124 I	1S35AC 2E P B	181	220-240 or 230	50/60	50/65
4	E124 I	1S35AC 2E T B	181	220-240 or 230	50/60	50/65
5	E124 I	1S35AC 2H P B	215	220-240 or 230	50/60	50/65
6	E124 I	1S35AC 2H T B	215	220-240 or 230	50/60	50/65
7	E124 I	1S40AC 2H T C	270	110	60	50/65
8	E124 I	1S40AE 2A P B	331	220-240 or 230	50/60	50/65
9	E124 I	1S40AE 2A T B	331	220-240 or 230	50/60	50/65
10	E124 I	1S40AE 2E P B	281	220-240 or 230	50/60	50/65
11	E124 I	1S40AE 2E T B	281	220-240 or 230	50/60	50/65
12	E124 I	1S40AE 2H P B	315	220-240 or 230	50/60	50/65
13	E124 I	1S40AE 2H T B	315	220-240 or 230	50/60	50/65
14	E124 I	1S40AF 2A P B	311	220-240 or 230	50/60	50/65
15	E124 I	1S40AF 2A T B	311	220-240 or 230	50/60	50/65
16	E124 I	1S40AF 2E P B	261	220-240 or 230	50/60	50/65
17	E124 I	1S40AF 2E T B	261	220-240 or 230	50/60	50/65
18	E124 I	1S40AF 2H P B	295	220-240 or 230	50/60	50/65
19	E124 I	1S40AF 2H T B	295	220-240 or 230	50/60	50/65
20	E124 I	1S40AC 2H T B	290	220-240 or 230	50/60	50/65
21	E124 I	1S40AC 2E T B	255	220-240 or 230	50/60	50/65
22	E124 I	1S40BF 2H T B	300	220-240 or 230 50 220	60	50/65
23	E124 I	1S40BF 2E T B	265	220-240 or 230 50 220	60	50/65
24	E124 I	1S48BD 2H T B	240	220-240 or 230	50/60	50/65
25	E124 I	1S48BD 2E T B	205	220-240 or 230	50/60	50/65
26	E124 I	1S35AC 2B P B	181	220-240 or 230	50/60	50/65
27	E124 I	1S35AC 2B T B	181	220-240 or 230 50 220	60	50/65
28	E124 I	1S35BB 2A P B	231	220-240 or 230 50 220	60	50/65
29	E124 I	1S35BB 2B P B	181	220-240 or 230 50 220	60	50/65
30	E124 I	1S35BB 2H P B	215	220-240 or 230 50 220	60	50/65
31	E124 I	1S35BB 2H T B	215	220-240 or 230 50 220	60	50/65

Additional information (if necessary)



- UL (US), 333 Pfingslen Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2018-05-08

Signature: 
Jan-Erik Storgaard

		Ref. Certif. No.																																																																																																																
		DK-72890-UL																																																																																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>No.</th> <th>Type</th> <th>Code (Electrical Configuration)</th> <th>Rated Input (W)</th> <th>Rated Voltage (V)</th> <th>Frequency (Hz)</th> <th>Distance from Electric/gas Hob (cm)</th> </tr> </thead> <tbody> <tr> <td rowspan="2">32</td> <td rowspan="2">E124 I</td> <td rowspan="2">1S35BB 2E P B</td> <td rowspan="2">180</td> <td>220-240 or 230</td> <td>50</td> <td rowspan="2">50/65</td> </tr> <tr> <td>220</td> <td>60</td> </tr> <tr> <td rowspan="2">33</td> <td rowspan="2">E124 I</td> <td rowspan="2">1S40BD 2A P B</td> <td rowspan="2">306</td> <td>220-240 or 230</td> <td>50</td> <td rowspan="2">50/65</td> </tr> <tr> <td>220</td> <td>60</td> </tr> <tr> <td rowspan="2">34</td> <td rowspan="2">E124 I</td> <td rowspan="2">1S40BD 2B P B</td> <td rowspan="2">256</td> <td>220-240 or 230</td> <td>50</td> <td rowspan="2">50/65</td> </tr> <tr> <td>220</td> <td>60</td> </tr> <tr> <td rowspan="2">35</td> <td rowspan="2">E124 I</td> <td rowspan="2">1S40BD 2E P B</td> <td rowspan="2">255</td> <td>220-240 or 230</td> <td>50</td> <td rowspan="2">50/65</td> </tr> <tr> <td>220</td> <td>60</td> </tr> <tr> <td rowspan="2">36</td> <td rowspan="2">E124 I</td> <td rowspan="2">1S35BB 2E T B</td> <td rowspan="2">180</td> <td>220-240 or 230</td> <td>50</td> <td rowspan="2">50/65</td> </tr> <tr> <td>220</td> <td>60</td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> Explanation of type/electrical configuration: </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> E124 = Type of construction </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> I = Insulation Class </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> xSy = Number of Motors and Type of Motor </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> xA, xH, xE or xB = Number and kind of lamps ("A" high voltage Halogen Lamps, "H" low voltage halogen lamps, "E" Spot Led Lamp or "B" Led Bulb Lamp). </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> P or T = Kind of Control ("P" Push Button or "T" Touch Control) </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> B or C = "B" tested for/at 240 V or "C" Voltage Ratings 110 V </td> </tr> <tr> <td colspan="7" style="text-align: left; padding-left: 20px;"> Remark: x is a number (one or more digit), y is a sequence of alphanumerical characters of any length. </td> </tr> </tbody> </table>							No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric/gas Hob (cm)	32	E124 I	1S35BB 2E P B	180	220-240 or 230	50	50/65	220	60	33	E124 I	1S40BD 2A P B	306	220-240 or 230	50	50/65	220	60	34	E124 I	1S40BD 2B P B	256	220-240 or 230	50	50/65	220	60	35	E124 I	1S40BD 2E P B	255	220-240 or 230	50	50/65	220	60	36	E124 I	1S35BB 2E T B	180	220-240 or 230	50	50/65	220	60	Explanation of type/electrical configuration:							E124 = Type of construction							I = Insulation Class							xSy = Number of Motors and Type of Motor							xA, xH, xE or xB = Number and kind of lamps ("A" high voltage Halogen Lamps, "H" low voltage halogen lamps, "E" Spot Led Lamp or "B" Led Bulb Lamp).							P or T = Kind of Control ("P" Push Button or "T" Touch Control)							B or C = "B" tested for/at 240 V or "C" Voltage Ratings 110 V							Remark: x is a number (one or more digit), y is a sequence of alphanumerical characters of any length.						
No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric/gas Hob (cm)																																																																																																												
32	E124 I	1S35BB 2E P B	180	220-240 or 230	50	50/65																																																																																																												
				220	60																																																																																																													
33	E124 I	1S40BD 2A P B	306	220-240 or 230	50	50/65																																																																																																												
				220	60																																																																																																													
34	E124 I	1S40BD 2B P B	256	220-240 or 230	50	50/65																																																																																																												
				220	60																																																																																																													
35	E124 I	1S40BD 2E P B	255	220-240 or 230	50	50/65																																																																																																												
				220	60																																																																																																													
36	E124 I	1S35BB 2E T B	180	220-240 or 230	50	50/65																																																																																																												
				220	60																																																																																																													
Explanation of type/electrical configuration:																																																																																																																		
E124 = Type of construction																																																																																																																		
I = Insulation Class																																																																																																																		
xSy = Number of Motors and Type of Motor																																																																																																																		
xA, xH, xE or xB = Number and kind of lamps ("A" high voltage Halogen Lamps, "H" low voltage halogen lamps, "E" Spot Led Lamp or "B" Led Bulb Lamp).																																																																																																																		
P or T = Kind of Control ("P" Push Button or "T" Touch Control)																																																																																																																		
B or C = "B" tested for/at 240 V or "C" Voltage Ratings 110 V																																																																																																																		
Remark: x is a number (one or more digit), y is a sequence of alphanumerical characters of any length.																																																																																																																		
<p>Factories:</p> <p>ELICA SPA LOCALITA MONTIRONE MERGO, 60030 AN Italy</p> <p>Additional Information: Additionally evaluated to: EN 60335-1:2012/A11:2014, EN 60335-2-31:2014, EN 62233:2008 National differences specified in the CB Test Report</p>																																																																																																																		
<p>Additional information (if necessary)</p> <p></p> <p> <input checked="" type="checkbox"/> UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA <input checked="" type="checkbox"/> UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK <input type="checkbox"/> UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN <input type="checkbox"/> UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA </p> <p style="text-align: right;">For full legal entity names see www.ul.com/ncbnames</p> <p>Date: 2018-05-08</p> <p>Signature:  Jan-Erik Storgaard</p>																																																																																																																		