

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	Range Hood
Name and address of the applicant	Elica SPA VIA ERMANNOCASOLI 2 FABRIANO, 60044 AN Italy
Name and address of the manufacturer	Elica SPA VIA ERMANNOCASOLI 2 FABRIANO, 60044 AN Italy
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	ELICA GROUP POLSKA SP Z O O UL INZYNIERSKA 3 JELCZ LASKOWICE, 55-221 Poland <input checked="" type="checkbox"/> Additional Information on page 3
Ratings and principal characteristics	220-240 or 230V 50-60Hz, 220-240 or 230V 50Hz, 220V 60Hz, 110-127V 60Hz, Max 306W See Page 2
Trademark (if any)	
Type of Customer's Testing Facility (CTF) Stage used	CTF Stage 3
Model / Type Ref.	E023B II See Page 2-3
Additional information (if necessary may also be reported on page 2)	<input checked="" type="checkbox"/> Additional Information on page 3
A sample of the product was tested and found to be in conformity with	IEC 60335-1:2010, IEC 60335-2-31:2012
As shown in the Test Report Ref. No. which forms part of this Certificate	19-4788895559.6.1 issued on 2019-05-03

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-05-20

Signature:

Jan-Erik Storgaard

Model Details:

Type/Code identification						
This Test Report covers the following type and associated code identifying the Electrical configuration: Type: E023B II + Code, (i.e. E023B II 1K30AD 2A P B)						
No.	Type	Code (Electrical Configuration)	Rated Input (W)	Rated Voltage (V)	Frequency (Hz)	Distance from Electric/gas Hob (cm)
1	E023B II	1K30AD 2A P B	176	220-240 or 230	50-60	50/65
2	E023B II	1K30AD 2A S B	176	220-240 or 230	50-60	50/65
3	E023B II	1K42AD 2A P B	236	220-240 or 230	50-60	50/65
4	E023B II	1K42AD 2A S B	236	220-240 or 230	50-60	50/65
5	E023B II	1S35AD 2A P B	236	220-240 or 230	50-60	50/65
6	E023B II	1S35AD 2A S B	236	220-240 or 230	50-60	50/65
7	E023B II	1S40AD 2A P B	306	220-240 or 230	50-60	50/65
8	E023B II	1S40AD 2A S B	306	220-240 or 230	50-60	50/65
9	E023B II	1K42AD 2H P C	240 *	110-127	60	65/65
10	E023B II	1S40AM 2A P B	306	220-240 or 230	50-60	50/65
11	E023B II	1S40AM 2A S B	306	220-240 or 230	50-60	50/65
12	E023B II	1K30AD 2B P B	126	220-240 or 230	50-60	50/65
13	E023B II	1K30AD 2B S B	126	220-240 or 230	50-60	50/65
14	E023B II	1K42AD 2B P B	186	220-240 or 230	50-60	50/65
15	E023B II	1K42AD 2B S B	186	220-240 or 230	50-60	50/65
16	E023B II	1S35AD 2B P B	186	220-240 or 230	50-60	50/65
17	E023B II	1S35AD 2B S B	186	220-240 or 230	50-60	50/65
18	E023B II	1S40AD 2B P B	256	220-240 or 230	50-60	50/65
19	E023B II	1S40AD 2B S B	256	220-240 or 230	50-60	50/65
20	E023B II	1S40AM 2B P B	256	220-240 or 230	50-60	50/65
21	E023B II	1S40AM 2B S B	256	220-240 or 230	50-60	50/65
22	E023B II	1K42AX 2B S B	146	220-240 or 230	50	50/65
				220	60	
				220	60	
23	E023B II	1K42AX 2B P B	146	220-240 or 230	50	50/65
				220	60	
24	E023B II	1S40AM 2E T B	255	220-240 or 230	50-60	50/65
25	E023B II	1S40AM 2E P B	255	220-240 or 230	50-60	50/65

Remark: *) 240 W refers to the whole rated voltage range 110-127 V. See Table 10.1 for acceptable deviation.

Additional information (if necessary)



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-05-20

Signature: 
Jan-Erik Storgaard

Model Details:

Explanation of type/electrical configuration:	
E023B	= Type of construction
II	= Insulation Class
xKy, xSy	= Number and kind of Motors
xA, xH, xB or xE	= Number and kind of lamps ("A" high voltage halogen lamps, "H" low voltage halogen lamps, "B" Led Bulb lamps or "E" Led Spot Lamp) ¹⁾
P, S or T	= Kind of Control ("P" Push Button, "S" Slider Switch or "T" Touch Controls)
B or C	= ("B") For UK (tested for/at 240V); Voltage Ratings ("C" for 110-127 V)
Remark: x is a number (one or more digit), y is alphanumerical string. ¹⁾ Without number on prefix indicates one lamp.	

Factories:

Elica SPA
Localita Montirone
Mergo, 60030 AN Italy

Additional Information:

Additionally evaluated to: EN 60335-1:2012/ A11:2014/ A13:2017, EN 60335-2-31:2014, EN 62233:2008 and IEC 60335-1:2010/A1:2013
National differences specified in the CB Test Report

Additional information (if necessary)



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/mcbnames

Date: 2019-05-20

Signature: 
Jan-Erik Storgaard