

Product Fiche compliant to commission delegated regulation (EU) No 65/2014 and UK SI 2019 No. 539

PRF0091761B

FOG0102648 Ed. 08/18

Table with 4 columns: Supplier's name or trade mark (ELICA), Model identifier (E023DII-025-003), Annual Energy Consumption - AEEhood (57.1 kWh/a), Energy Efficiency Class (D), Fluid Dynamic Efficiency - FDEhood (9.2 %), Fluid Dynamic Efficiency class (E), Light Efficiency - LEhood (16.1 lux/W), Lighting Efficiency Class (C), Grease Filtering Efficiency - GFEhood (66 %), Grease Filtering Efficiency class (D), Minimum Air Flow in normal use (165 m³/h), Maximum Air Flow in normal use (395 m³/h), Air Flow at intensive/boost setting (NA m³/h), A-weighted Sound Power Emission at minimum speed (49 dB(A) re 1pW), A-weighted Sound Power Emission at maximum speed (68 dB(A) re 1pW), A-weighted Sound Power Emission at intensive or boost speed (NA dB(A) re 1pW), Power consumption off mode - Po (NA W), Power consumption in standby mode - Ps (NA W). Each row includes detailed technical specifications in multiple languages.

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with 4 columns: Time increase factor (f, 1.7), Energy Efficiency Index (EELhood, 87.3), Measured air flow rate at best efficiency point (QBEP, 224 m³/h), Measured air pressure at best efficiency point (PBEP, 125 Pa), Maximum air flow (Qmax, 395 m³/h), Measured electric power input at best efficiency point (WBEP, 85 W), Nominal power of the lighting system (WL, 6 W), Average illumination of the lighting system on the cooking surface (Emiddle, 97 lux). Each row includes detailed technical specifications in multiple languages.

