

Table with 4 columns: Supplier's name or trade mark, Value, Unit, and description of the regulation requirement in multiple languages.

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with 4 columns: Symbol, Value, Unit, and description of the regulation requirement in multiple languages.

Product Fiche compliant to commission delegated regulation (EU) No 65/2014 and UK SI 2019 No. 539

PRF0156613A FOG0102648 Ed. 08/18

Table with columns: Supplier's name or trade mark (ELICA), Model identifier (E017EXI-034-001), Annual Energy Consumption - AEEhood (48.5 kWh/a), Energy Efficiency Class (A), Fluid Dynamic Efficiency - FDEhood (29.6 %), Fluid Dynamic Efficiency class (A), Light Efficiency - LEhood (76.1 lux/W), Lighting Efficiency Class (A), Grease Filtering Efficiency - GFEhood (65.1 %), Grease Filtering Efficiency class (D), Minimum Air Flow in normal use (160 m³/h), Maximum Air Flow in normal use (560 m³/h), Air Flow at intensive/boost setting (680 m³/h), A-weighted Sound Power Emission at minimum speed (34 dB(A) re 1pW), A-weighted Sound Power Emission at maximum speed (66 dB(A) re 1pW), A-weighted Sound Power Emission at intensive or boost speed (70 dB(A) re 1pW), Power consumption off mode - Po (NA W), Power consumption in standby mode - Ps (0.49 W)

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with columns: Symbol, Value, Unit, and description. Includes rows for Time increase factor (f, 0.9), Energy Efficiency Index (EEIhood, 52.1), Measured air flow rate at best efficiency point (QBEP, 355 m³/h), Measured air pressure at best efficiency point (PBEP, 410 Pa), Maximum air flow (Qmax, 680 m³/h), Measured electric power input at best efficiency point (WBEP, 136.5 W), Nominal power of the lighting system (WL, 5 W), Average illumination of the lighting system on the cooking surface (Emiddle, 381 lux)