

Table with columns: Supplier's name or trade mark, Model identifier, Annual Energy Consumption - AEC'hood, Energy Efficiency Class, Fluid Dynamic Efficiency - FDE'hood, Fluid Dynamic Efficiency class, Light Efficiency - LE'hood, Lighting Efficiency Class, Grease Filtering Efficiency - GFE'hood, Grease Filtering Efficiency class, Minimum Air Flow in normal use, Maximum Air Flow in normal use, Air Flow at intensive/boost setting, A-weighted Sound Power Emission at minimum speed, A-weighted Sound Power Emission at maximum speed, A-weighted Sound Power Emission at intensive or boost speed, Power consumption off mode - Po, Power consumption in standby mode - Ps. Values include ELICA, E122EXI-007-001, 46, A, 33.8, A, 52.1, A, 55.1, E, 285, 560, 700, 51, 66, 71, NA, 0.49.

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with columns: Symbol, Value, Unit. Rows include: Time increase factor (f, 0.8), Energy Efficiency Index (EEl'hood, 47.8), Measured air flow rate at best efficiency point (QBEP, 370), Measured air pressure at best efficiency point (PBEP, 460), Maximum air flow (Qmax, 700), Measured electric power input at best efficiency point (WBEP, 140), Nominal power of the lighting system (WL, 7), Average illumination of the lighting system on the cooking surface (Emiddle, 365).

