



Product Fiche compliant to commission delegated regulation (EU) No 65/2014 and UK SI 2019 No. 539

PRF0183060

FOG0102648 Ed. 08/18

Table with columns: Supplier's name or trade mark (ELICA), Model identifier (E105XXI-004-001), Annual Energy Consumption - AEC hood (62.8 kWh/a), Energy Efficiency Class (B), Fluid Dynamic Efficiency - FDE hood (27.8%), Fluid Dynamic Efficiency class (B), Light Efficiency - LE hood (76.1 lux/W), Lighting Efficiency Class (A), Grease Filtering Efficiency - GFE hood (75.1%), Grease Filtering Efficiency class (C), Minimum Air Flow in normal use (275 m³/h), Maximum Air Flow in normal use (510 m³/h), Air Flow at intensive/boost setting (650 m³/h), A-weighted Sound Power Emission at minimum speed (49 dB(A) re 1pW), A-weighted Sound Power Emission at maximum speed (63 dB(A) re 1pW), A-weighted Sound Power Emission at intensive or boost speed (68 dB(A) re 1pW), Power consumption off mode - Po (NA W), Power consumption in standby mode - Ps (0.49 W)

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with columns: Time increase factor (f, 1), Energy Efficiency Index (EEI hood, 59.4), Measured air flow rate at best efficiency point (QBEP, 370 m³/h), Measured air pressure at best efficiency point (PBEP, 425 Pa), Maximum air flow (Qmax, 650 m³/h), Measured electric power input at best efficiency point (WBEP, 157 W), Nominal power of the lighting system (WL, 7.5 W), Average illumination of the lighting system on the cooking surface (Emiddle, 571 lux)