User Manual Energy Efficiency

| Annual Energy Consumption - AEChood 75 Energy Efficiency Class B Fluid Dynamic Efficiency - FDEhood 20.9 Fluid Dynamic Efficiency class C Light Efficiency - Lehood 44.1 Lighting Efficiency Class A Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at 56 A-weighted Sound Power Emission at 57 A-weighted Sound Power Emission at 57 A-weighted Sound Power Emission at 58 A-weighted Sound Power Emission at 58 A-weighted Sound Power Emission at 59 A-weighted | | |
|--|-----------------|--------------|
| Annual Energy Consumption - AEChood 75 Energy Efficiency Class B Fluid Dynamic Efficiency - FDEhood 20.9 Fluid Dynamic Efficiency class C Light Efficiency - LEhood 44.1 Lighting Efficiency Class A Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at 54 A-weighted Sound Power Emission at 55 A-weighted | Elica | |
| Energy Efficiency Class B Fluid Dynamic Efficiency - FDEhood 20.9 Fluid Dynamic Efficiency class C Light Efficiency - LEhood 44.1 Lighting Efficiency Class A Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings A-weighted Sound Power Emission at | E017GXI-002-001 | |
| Fluid Dynamic Efficiency - FDEhood 20.9 Fluid Dynamic Efficiency class C Light Efficiency - LEhood 44.1 Lighting Efficiency Class A Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at 55 A-weighted Soun | | KWh/a |
| Fluid Dynamic Efficiency class C Light Efficiency - LEhood Lighting Efficiency Class A Grease Filtering Efficiency - GFEhood Grease Filtering Efficiency class C Minimum Air Flow in normal use Maximum Air Flow in normal use A-weighted Sound Power Emission at A-weighted Sound | | |
| Light Efficiency - LEhood 44.1 Lighting Efficiency Class A Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at 55 A-weighted Sound Power Emission at 75 A-weighted Sound Power Emission at 7 | 9 | |
| Lighting Efficiency Class Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EElhood A75.1 A75. | | |
| Grease Filtering Efficiency - GFEhood 75.1 Grease Filtering Efficiency class C Minimum Air Flow in normal use 225 Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at 65 A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps 0.45 Additional Info. according to UK SI 2019 No. 539 Time increase factor - f 1.2 Energy Efficiency Index - EEIhood 69.6 | 1 | lux/W |
| Grease Filtering Efficiency class C Minimum Air Flow in normal use Air Flow at intensive/boost settings A-weighted Sound Power Emission at Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f 1.2 Energy Efficiency Index - EEIhood | | lux |
| Minimum Air Flow in normal use Maximum Air Flow in normal use Air Flow at intensive/boost settings A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EElhood 580 NA According to UK SI 2019 No. 539 1.2 | 1 | % |
| Maximum Air Flow in normal use 580 Air Flow at intensive/boost settings NA A-weighted Sound Power Emission at 46 A-weighted Sound Power Emission at 65 A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps 0.49 Additional Info. according to UK SI 2019 No. 539 Time increase factor - f 1.2 Energy Efficiency Index - EElhood 69.6 | | |
| Air Flow at intensive/boost settings A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f 1.2 Energy Efficiency Index - EEIhood | j | m3/h |
| A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EElhood 46 46 47 48 48 48 48 48 48 48 48 48 |) | m3/h |
| A-weighted Sound Power Emission at A-weighted Sound Power Emission at NA Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EEIhood 65 NA NA NA 1.2 | | m3/h |
| A-weighted Sound Power Emission at Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EEIhood NA NA 1.2 | | db(A) re_1pW |
| Power consumption off mode - Po NA Power consumption in standby mode - Ps Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EEIhood NA 1.2 | | db(A) re_1pW |
| Power consumption in standby mode - Ps 0.49 Additional Info. according to UK SI 2019 No. 539 Time increase factor - f 1.2 Energy Efficiency Index - EEIhood 69.6 | | db(A) re_1pW |
| Additional Info. according to UK SI 2019 No. 539 Time increase factor - f Energy Efficiency Index - EEIhood 69.6 | | W |
| Time increase factor - f 1.2 Energy Efficiency Index - EEIhood 69.6 | 9 | W |
| Energy Efficiency Index - EEIhood 69.6 | | |
| | | |
| | 6 | |
| Measured air flow rate at best efficiency 345 | 5 | m3/h |
| Measured air pressure at best efficiency 355 | j i | Pa |
| Maximum air flow - Qmax NA | | m3/h |
| Measured electric power input at best 163 | 3 | W |
| Nominal power of the lighting system - WL 5 | | W |
| Average illumination of the lighting system 221 | | lux |

Appliance designed, tested and manufactured according to: • Performance: BS EN IEC 61591; BS EN ISO 5167-1; BS EN ISO 5167-3; BS ISO 5168; BS EN 60704-1; BS EN 60704-2-13; BS EN ISO 3741; BS EN 50564; BS EN 62301. Suggestions for a correct use in order to reduce the environmental impact: • Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is finished. • Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations. • Replace the charcoal filter(s) when necessary to maintain a good grease filter efficiency. • Use the maximum diameter of the ducting system indicated in this manual to optimize efficiency and minimize noise.