## User Manual Energy Efficiency

Product Fiche according to UK SI 2019 No. 539			
Supplier's name or trade mark	Elica	Elica	
Model identifier	HI03XXI-00	HI03XXI-008-001	
Annual Energy Consumption - AEChood	37.2	KWh/a	
Energy Efficiency Class	A+		
Fluid Dynamic Efficiency - FDEhood	35.7		
Fluid Dynamic Efficiency class	A		
Light Efficiency - LEhood	NA	lux/W	
Lighting Efficiency Class	NA	lux	
Grease Filtering Efficiency - GFEhood	75.1	%	
Grease Filtering Efficiency class	С		
Minimum Air Flow in normal use	135	m3/h	
Maximum Air Flow in normal use	375	m3/h	
Air Flow at intensive/boost settings	630	m3/h	
A-weighted Sound Power Emission at	33	db(A) re_1pW	
A-weighted Sound Power Emission at	59	db(A) re_1pW	
A-weighted Sound Power Emission at	71	db(A) re_1pW	
Power consumption off mode - Po	0.49	W	
Power consumption in standby mode - Ps	NA	W	
Additional Info. according to UK SI 2019 No. 539	·	•	
Time increase factor - f	0.7		
Energy Efficiency Index - EElhood	39		
Measured air flow rate at best efficiency	340	m3/h	
Measured air pressure at best efficiency	550	Pa	
Maximum air flow - Qmax	NA	m3/h	
Measured electric power input at best	145.5	W	
Nominal power of the lighting system - WL	0	W	
Average illumination of the lighting system		lux	

Appliance designed, tested and manufactured according to: • Performance: BS EN IEC 61591; BS EN ISO 5167-1; BS EN ISO 5167-3; BS ISO 5168; BS EN 60704-1; BS EN 60704-2-13; BS EN ISO 3741; BS EN 50564; BS EN 62301. Suggestions for a correct use in order to reduce the environmental impact: • Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is finished. • Increase the speed only in case of large amount of smoke and vapour and use boost speed(s) only in extreme situations. • Replace the charcoal filter(s) when necessary to maintain a good grease filter efficiency. • Use the maximum diameter of the ducting system indicated in this manual to optimize efficiency and minimize noise.