

	Value	Unit
Supplier's name or trade mark	ELICA	
Model identifier	H104XXI-005-001	
Annual Energy Consumption - AEEhood	31.9	kWh/a
Energy Efficiency Class	A	
Fluid Dynamic Efficiency - FDEhood	26.7	%
Fluid Dynamic Efficiency class	B	
Light Efficiency - LEhood	NA	lux/W
Lighting Efficiency Class	NA	lux
Grease Filtering Efficiency - GFEhood	65.1	%
Grease Filtering Efficiency class	D	
Minimum Air Flow in normal use	205.0	m <sup>3</sup> /h
Maximum Air Flow in normal use	455.0	m <sup>3</sup> /h
Air Flow at intensive/boost setting	570.0	m <sup>3</sup> /h
A-weighted Sound Power Emission at minimum speed	43.0	dB(A) re 1pW
A-weighted Sound Power Emission at maximum speed	61.0	dB(A) re 1pW
A-weighted Sound Power Emission at intensive or boost speed	67.0	dB(A) re 1pW
Power consumption off mode - P <sub>o</sub>	0.49	W
Power consumption in standby mode - P <sub>s</sub>	NA	W

## Additional info. according to UK SI 2019 No. 539

	Value	Unit
Time increase factor	1.0	
Energy Efficiency Index	50.3	
Measured air flow rate at best efficiency point	255.0	m <sup>3</sup> /h
Measured air pressure at best efficiency point	330.0	Pa
Maximum air flow	NA	m <sup>3</sup> /h
Measured electric power input at best efficiency point	87.5	W
Nominal power of the lighting system	0.0	W
Average illumination of the lighting system on the cooking surface		lux

Appliance designed, tested and manufactured according to: Safety: BS EN 60335-1; BS EN 60335-2-31, BS EN 62233.. Performance: BS EN IEC 61591; BS EN ISO 5167-1; BS EN ISO 5167-3; BS ISO 5168; BS EN 60704-1; BS EN 60704-2-13; BS EN ISO 3741; BS EN 50564; BS EN 62301. EMC: BS EN 55014-1; CISPR 14-1; BS EN 55014-2; CISPR 14-2; BS EN 61000-3-2; BS EN 61000-3-3. Suggestions for a correct use in order to reduce the environmental impact: Switch ON the hood at minimum speed when you start cooking and kept it running for few minutes after cooking is finished.. Increase the speed only in ca in extreme situations. Replace the charcoal filter(s) when necessary to maintain a good odour reduction efficiency.. Clean the grease filter(s) when necessary to maintain a good grease filter efficiency. Use the maximum diameter of the ducting system indicated in this manual to optimize efficiency and minimize noise.