



User Interface

Motor (M) (Family S40 024 xx)

Speed	Colors	Resistance at 22°C (Ohm) Min - Max
1	Blue - White	108,1 - 119,5
2	Blue - Red	94,3 - 104,2
3	Blue - Grey	80,3 - 88,8
4	Blue - Black	62,7 - 69,3

Connectors

Connector	Pole Number	Function	Voltage
C1	1 (Blue)	Power In	230 VAC
	3 (Brown)		
C2	1 (Black)	4° Speed	230 VAC
	2 (White)	1° Speed	230 VAC
	3 (Grey)	3° Speed	230 VAC
	4 (Red)	2° Speed	230 VAC
	5 (Blue)	Common	---
C3	1 (Black)	Light Power	GND
	3 (Red)		12 VDC
C4	1 (Red)	Command Communication	GND
	2 (Grey)		DATA
	3 (Grey)		DATA
	4 (Grey)		DATA
	5 (Grey)		12 VDC
	6 (Grey)		DATA

SEL0204742

DATA DATE	MODIF. N. MODIF. NO.	DESCRIZIONE MODIFICA MODIFICATION	DISegnATO DRAWN BY	APPROVATO APPROVED
MODELLO MODEL	PARTICOLARE DETAIL		DISegnO N. DRAWING No.	DATA DATE
STRIPE / VARIOUS		<i>Schema elettrico / Wiring diagram</i>	SEL0204742	
MATERIALE MATERIAL			DISegnATO DRAWN BY	26/09/2024
<i>Carta adesiva bianca 150x200 / Sticky white paper 150x200</i>			<i>Salvucci L.</i>	
elica		COLORE STAMPA PRINT COLOUR	APPROVATO APPROVED	
UFFICIO TECNICO TECHNICAL DEPARTMENT		Nero / Black	<i>Garufi C.</i>	
SCALA SCALE	LA RIPRODUZIONE O LA CESSIONE DEL PRESENTE DISEGNO DEVONO ESSERE AUTORIZZATE DALLA "ELICA" SPA		SOSTITUITO DAL DIS. N. REPLACED BY DRAWING	ULTIMA EMISS. LAST EDITION
FORM. A-4	1:1	ANY REPRODUCTION OR TRANSFER OF THE PRESENT DRAWING MUST BE AUTHORIZED BY "ELICA" SPA.	SOSTITUISCE IL DIS. N. IT REPLACES DRAWING	25/09/2024

QUOTE SENZA TOLLERANZA TOLLERANCE UNLESS OTHERWISE STATED
 QUOTA PRIMARIA PRIMARY DIMENSION XX
 ANGOLI Angles ± 0° 30'